


Obturbateur male série L et S



RACCORD DIN CONE 24°

Matière: acier

Norme: ISO 8434-1 (DIN 2353)

Type: 1080

Raccord livré nu, sans bague et sans ecrou

Code	Référence	D1	D2	D3	Pression (Bar)	Poids
SERIE L						
000908	18DL 6 NU	6L - M12X150			315	0
000909	18DL 8 NU	8L - M14X150			315	0
000910	18DL10 NU	10L - M16X150			315	0
000911	18DL12 NU	12L - M18X150			315	0.008
000912	18DL15 NU	15L - M22X150			315	0.039
000913	18DL18 NU	18L - M26X150			315	0
000914	18DL22 NU	22L - M30X200			160	0
000915	18DL28 NU	28L - M36X200			160	0
000916	18DL35 NU	35L - M45X200			160	0
025056	18DL42 NU	42L - M52X200			160	0
SERIE S						
000917	18DS 6 NU	6S - M14X150			630	0
000918	18DS 8 NU	8S - M16X150			630	0
000919	18DS10 NU	10S - M18X150			630	0
000920	18DS12 NU	12S - M20X150			630	0
000921	18DS14 NU	14S - M22X150			630	0
000922	18DS16 NU	16S - M24X150			400	0
000923	18DS20 NU	20S - M30X200			400	0
000924	18DS25 NU	25S - M36X200			400	0
000925	18DS30 NU	30S - M42X200			400	0
000926	18DS38 NU	38S - M52X200			315	0