


Embout à sertir 45° femelle PRISE DE PRESSION



POUR PRISE DE PRESSION (45°)

Matière: acier
Montage: sans dénudage
Norme: pour mesure de pression

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
083554	S R 2 FT 12,65X150 45°	2	1/12"	M12X150				0
035560	S R 2 FT 16X150 45°	2	1/12"	M16X150				0.032
035563	S R 2 FT 16X200 45°	2	1/12"	M16X200				0.032
083577	S R 3 FT 12,65X150 45°	3	1/8"	M12X150				0
035561	S R 3 FT 16X150 45°	3	1/8"	M16X150				0.038
035564	S R 3 FT 16X200 45°	3	1/8"	M16X200				0.038
083580	S R 4 FT 12,65X150 45°	4	5/32"	M12X150				0
035562	S R 4 FT 16X150 45°	4	5/32"	M16X150				0.05
035565	S R 4 FT 16X200 45°	4	5/32"	M16X200				0.05
083835	S R 2 FT6P 16X150 45°	2	1/12"	M16X150				0.032
083832	S R 2 FT6P 16X200 45°	2	1/12"	M16X200				0.032
083842	S R 3 FT6P 16X150 45°	3	1/8"	M16X150				0.038
083839	S R 3 FT6P 16X200 45°	3	1/8"	M16X200				0.038
083848	S R 4 FT6P 16X150 45°	4	5/32"	M16X150				0.05
083845	S R 4 FT6P 16X200 45°	4	5/32"	M16X200				0.05