


Embout à sertir 90° à bride 6000 PSI



SFS - COLLET SAE 6000 PSI

Matière: Acier

Montage: Avec ou sans dénudage

Norme: SAE J518 - serie 6000 psi

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
011806	S R 13 CF 1/2 90°	13	1/2"	1/2"		31.8mm	7.8mm	0.115
011809	S R 13 CF 3/4 90°	13	1/2"	3/4"		41.3mm	8.8mm	0.185
011978	S R 16 CF 1/2 90°	16	5/8"	1/2"		31.8mm	7.8mm	0.15
011981	S R 16 CF 3/4 90°	16	5/8"	3/4"		41.3mm	8.8mm	0.216
068159	S R 16 CF 1" 90°	16	5/8"	1"		47.6mm	9.5mm	0.15
012111	S R 19 CF 1/2 90°	19	3/4"	1/2"		31.8mm	7.8mm	0.2
012114	S R 19 CF 3/4 90°	19	3/4"	3/4"		41.3mm	8.8mm	0.236
012108	S R 19 CF 1" 90°	19	3/4"	1"		47.6mm	9.5mm	0.29
122379	S R 19 CF 1"1/4 90°	29	3/4"	1"1/4		54.0mm	10.3mm	0.417
012255	S R 25 CF 3/4 90°	25	1"	3/4"		41.3mm	8.8mm	0.38
012249	S R 25 CF 1" 90°	25	1"	1"		47.6mm	9.5mm	0.439
012252	S R 25 CF 1"1/4 90°	25	1"	1"1/4		54.0mm	10.3mm	0.524
012360	S R 32 CF 1" 90°	32	1"1/4	1"		47.6mm	9.5mm	0
012363	S R 32 CF 1"1/4 90°	32	1"1/4	1"1/4		54.0mm	10.3mm	0.666
108609	S R 32 CF 1"1/2 90°	32	1"1/4	1"1/2		63.5mm	12.6mm	1.025
108616	S R 38 CF 1"1/4 90°	38	1"1/2	1"1/4		54mm	10.3mm	0
012450	S R 38 CF 1"1/2 90°	38	1"1/2	1"1/2		63.5mm	12.6mm	0.962
108613	S R 38 CF 2" 90°	38	1"1/2	2"		79.4mm	12.6mm	1.83
012512	S R 50 CF 2" 90°	50	2"	2"		79.4mm	12.6mm	1.982