


Embout à sertir 90° femelle MÉTRIQUE cone 60°



DKM - DIN CONE 60°

Matière: Acier

Montage: Avec ou sans dénudage

Norme: ISO 8434-6 - DIN 3863

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
038120	S R 5 DF 12 90°	5	3/16"	M12X150				0.034
038121	S R 6 DF 12 90°	6	1/4"	M12X150				0.037
038122	S R 6 DF 14 90°	6	1/4"	M14X150				0.04
038123	S R 6 DF 16 90°	6	1/4"	M16X150				0.056
038124	S R 6 DF 18 90°	6	1/4"	M18X150				0.052
038125	S R 8 DF 14 90°	8	5/16"	M14X150				0.055
038126	S R 8 DF 16 90°	8	5/16"	M16X150				0.066
038127	S R 8 DF 18 90°	8	5/16"	M18X150				0.062
038128	S R 10 DF 14 90°	10	3/8"	M14X150				0.071
038129	S R 10 DF 16 90°	10	3/8"	M16X150				0.103
038130	S R 10 DF 18 90°	10	3/8"	M18X150				0.098
038131	S R 10 DF 20 90°	10	3/8"	M20X150				0.099
038132	S R 10 DF 22 90°	10	3/8"	M22X150				0.093
038133	S R 13 DF 18 90°	13	1/2"	M18X150				0.119
038134	S R 13 DF 20 90°	13	1/2"	M20X150				0.118
038135	S R 13 DF 22 90°	13	1/2"	M22X150				0.113
038136	S R 13 DF 26 90°	13	1/2"	M26X150				0.167
038560	S R 16 DF 26 90°	16	5/8"	M26X150				0.195
012126	S R 19 DF 26 90°	19	3/4"	M26X150				0.216
012129	S R 19 DF 30 90°	19	3/4"	M30X200				0
038561	S R 25 DF 38 90°	25	1"	M38X150				0.61
012374	S R 32 DF 45 90°	32	1 1/4"	M45X150				0.63