


Embout à sertir 90° femelle DIN S



DKOS 90° - CONE 24° - SERIE LOURDE AVEC JOINT

Matière: Acier
Montage: Avec ou sans dénudage
Norme: ISO 8434-1 (DIN 2353).

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
035429	S R 2 EFR 6 S 90°	2	1/12"	6S - M14X150				0.026
035430	S R 2 EFR 8 S 90°	2	1/12"	8S - M16X150				0.034
035431	S R 2 EFR 10 S 90°	2	1/12"	10S - M18X150				0.045
035432	S R 3 EFR 6 S 90°	3	1/8"	6S - M14X150				0.028
035433	S R 3 EFR 8 S 90°	3	1/8"	8S - M16X150				0.039
035434	S R 3 EFR 10 S 90°	3	1/8"	10S - M18X150				0.045
035435	S R 4 EFR 6 S 90°	4	5/32"	6S - M14X150				0.02
035436	S R 4 EFR 8 S 90°	4	5/32"	8S - M16X150				0.035
035437	S R 4 EFR 10 S 90°	4	5/32"	10S - M18X150				0.034
035438	S R 4 EFR 12 S 90°	4	5/32"	12S - M20X150				0.045
026095	S R 5 EFR 6 S 90°	5	3/16"	6S - M14X150				0.389
011360	S R 5 EFR 8 S 90°	5	3/16"	8S - M16X150				0.041
011420	S R 6 EFR 6 S 90°	6	1/4"	6S - M14X150				0.043
011426	S R 6 EFR 8 S 90°	6	1/4"	8S - M16X150				0.043
011410	S R 6 EFR 10 S 90°	6	1/4"	10S - M18X150				0.055
011414	S R 6 EFR 12 S 90°	6	1/4"	12S - M20X150				0.063
108556	S R 8 EFR 8 S 90°	8	5/16"	8S - M16X150				0.06
011549	S R 8 EFR 10 S 90°	8	5/16"	10S - M18X150				0.062
011557	S R 8 EFR 12 S 90°	8	5/16"	12S - M20X150				0.069
011560	S R 8 EFR 14 S 90°	8	5/16"	14S - M22X150				0.09
021348	S R 10 EFR 10 S 90°	10	3/8"	10S - M18X150				0.064
011675	S R 10 EFR 12 S 90°	10	3/8"	12S - M20X150				0.075
011678	S R 10 EFR 14 S 90°	10	3/8"	14S - M22X150				0.104
011684	S R 10 EFR 16 S 90°	10	3/8"	16S - M24X150				0.11
038718	S R 13 EFR 12 S 90°	13	1/2"	12S - M20X150				0.095
011827	S R 13 EFR 14 S 90°	13	1/2"	14S - M22X150				0.13
011834	S R 13 EFR 16 S 90°	13	1/2"	16S - M24X150				0.139
011840	S R 13 EFR 20 S 90°	13	1/2"	20S - M30X200				0.19
012004	S R 16 EFR 16 S 90°	16	5/8"	16S - M24X150				0.17
012010	S R 16 EFR 20 S 90°	16	5/8"	20S - M30X200				0.224
012016	S R 16 EFR 25 S 90°	16	5/8"	25S - M36X200				0.36
125294	S R 16 EFR 30 S 90°	16	5/8"	30S - M42X200				0.43
012146	S R 19 EFR 20 S 90°	19	3/4"	20S - M30X200				0.262
054470	S R 19 EFR 25 S 90°	19	3/4"	25S - M36X200				0.389
012159	S R 19 EFR 30 S 90°	19	3/4"	30S - M42X200				0.47
012280	S R 25 EFR 25 S 90°	25	1"	25S - M36X200				0.595

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
012286	S R 25 EFR 30 S 90°	25	1"	30S - M42X200				0.578
012292	S R 25 EFR 38 S 90°	25	1"	38S - M52X200				0.7
012387	S R 32 EFR 30 S 90°	32	1"1/4	30S - M42X200				0.73
012393	S R 32 EFR 38 S 90°	32	11/4"	38S - M52X200				0.858
012472	S R 38 EFR 38 S 90°	38	1"1/2	38S - M52X200				0.96
038746	S R 38 EFR 50 S 90°	38	1"1/2	50S - M68X200				1.4