


Embout à sertir 90° femelle PRISE DE PRESSION



POUR PRISE DE PRESSION 90°

Matière: acier
Montage: sans dénudage
Norme: pour mesure de pression

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
053739	S R 2 FT 12,65X150 90°	2	1/12"	M12X150				0
035557	S R 2 FT 16X150 90°	2	1/12"	M16X150				0.032
022903	S R 2 FT 16X200 90°	2	1/12"	M16X200				0.032
083836	S R 2 FT6P 16X150 90°	2	1/12"	M16X150				0.032
083833	S R 2 FT6P 16X200 90°	2	1/12"	M16X200				0.032
083578	S R 3 FT 12,65X150 90°	3	1/8"	M12X150				0
035558	S R 3 FT 16X150 90°	3	1/8"	M16X150				0.038
035555	S R 3 FT 16X200 90°	3	1/8"	M16X200				0.038
083843	S R 3 FT6P 16X150 90°	3	1/8"	M16X150				0.038
083840	S R 3 FT6P 16X200 90°	3	1/8"	M16X200				0.038
083581	S R 4 FT 12,65X150 90°	4	5/32"	M12X150				0
035559	S R 4 FT 16X150 90°	4	5/32"	M16X150				0.05
035556	S R 4 FT 16X200 90°	4	5/32"	M16X200				0.05
083849	S R 4 FT6P 16X150 90°	4	5/32"	M16X150				0.05
083846	S R 4 FT6P 16X200 90°	4	5/32"	M16X200				0.05