


Embout à sertir 90° femelle JIC - écrou à jonc



DKJ 90° - CONE 74° - AVEC ECROU A JONC

Matière: Acier

Montage: Avec ou sans dénudage

Norme: ISO 8434-2 (SAE J514).

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
038592	S R 5 JFJ 7/16 90°	5	3/16"	7/16 - 20				0.029
038593	S R 5 JFJ 1/2 90°	5	3/16"	1/2 - 20				0.037
038594	S R 6 JFJ 7/16 90°	6	1/4"	7/16 - 20				0.031
038595	S R 6 JFJ 1/2 90°	6	1/4"	1/2 - 20				0.04
038596	S R 6 JFJ 9/16 90°	6	1/4"	9/16 - 18				0.049
038597	S R 8 JFJ 9/16 90°	8	5/16"	9/16 - 18				0.058
137303	S R 8 JFJ 1/2 90°	8	5/16"	1/2 - 20				0.05
137304	S R 8 JFJ 3/4 90°	8	5/16"	3/4 - 16				0.05
038598	S R 10 JFJ 9/16 90°	10	3/8"	9/16 - 18				0.065
038599	S R 10 JFJ 3/4 90°	10	3/8"	3/4 - 16				0.08
038600	S R 10 JFJ 7/8 90°	10	3/8"	7/8 - 14				0.115
038601	S R 13 JFJ 3/4 90°	13	1/2"	3/4 - 16				0.096
038602	S R 13 JFJ 7/8 90°	13	1/2"	7/8 - 14				0.137
038603	S R 13 JFJ 1"1/16 90°	13	1/2"	1"1/16 - 12				0.165
038604	S R 16 JFJ 7/8 90°	16	5/8"	7/8 - 14				0.166
038605	S R 16 JFJ 1"1/16 90	16	5/8"	1"1/16 - 12				0.202
031421	S R 19 JFJ 1"1/16 90°	19	3/4"	1"1/16 - 12				0.223
038606	S R 19 JFJ 1"3/16 90°	19	3/4"	1"3/16 - 12				0.185
038608	S R 19 JFJ 1"5/16 90°	19	3/4"	1"5/16 - 12				0.325
137472	S R 19 JFJ 7/8 90°	19	3/4"	7/8 - 14				0.232
137474	S R 25 JFJ 1"1/16 90°	25	1"	1"1/16 - 12				0.498
031424	S R 25 JFJ 1"5/16 90	25	1"	1"5/16 - 12				0.474
012326	S R 25 JFJ 1"5/8 90°	25	1"	1"5/8 - 12				0.591
012421	S R 32 JFJ 1"5/8 90°	32	1"1/4	1"5/8 - 41				0.737
012424	S R 32 JFJ 1"7/8 90°	32	1"1/4	1"7/8 - 12				1.002
012490	S R 38 JFJ 1"7/8 90°	38	1"1/2	1"7/8 - 12				1.17
137488	S R 38 JFJ 2"1/2 90°	38	1"1/2	2"1/2 - 12				1.713
012533	S R 50 JFJ 2"1/2 90°	50	2"	2"1/2 - 12				2.147