


Embout à sertir 90° femelle BSP - écrou serti



DKR 90° - CONE 60° - AVEC ECROU SERTI

Matière: Acier
Montage: Avec ou sans dénudage
Norme: ISO 8434-6 (BS 5200).

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
035448	S R 2 WF 1/8 90°	2	1/12"	1/8"				0.02
035449	S R 2 WF 1/4 90°	2	1/12"	1/4"				0.03
035450	S R 3 WF 1/8 90°	3	1/8"	1/8"				0.022
035451	S R 3 WF 1/4 90°	3	1/8"	1/4"				0.031
035452	S R 4 WF 1/8 90°	4	5/32"	1/8"				0.02
035453	S R 4 WF 1/4 90°	4	5/32"	1/4"				0.035
011388	S R 5 WF 1/8 90°	5	3/16"	1/8"				0.028
011386	S R 5 WF 1/4 90°	5	3/16"	1/4"				0.038
011509	S R 6 WF 1/8 90°	6	1/4"	1/8"				0.031
011504	S R 6 WF 1/4 90°	6	1/4"	1/4"				0.041
011512	S R 6 WF 3/8 90°	6	1/4"	3/8"				0.055
062775	S R 6 WF 1/2 90°	6	1/4"	1/2"				0
011635	S R 8 WF 1/4 90°	8	5/16"	1/4"				0.056
011638	S R 8 WF 3/8 90°	8	5/16"	3/8"				0.065
062776	S R 8 WF 1/2 90°	8	5/16"	1/2"				0
011775	S R 10 WF 1/4 90°	10	3/8"	1/4"				0.072
011778	S R 10 WF 3/8 90°	10	3/8"	3/8"				0.101
011771	S R 10 WF 1/2 90°	10	3/8"	1/2"				0.097
011942	S R 13 WF 3/8 90°	13	1/2"	3/8"				0.122
011935	S R 13 WF 1/2 90°	13	1/2"	1/2"				0.116
011945	S R 13 WF 5/8 90°	13	1/2"	5/8"				0.142
011939	S R 13 WF 3/4 90°	13	1/2"	3/4"				0.164
012086	S R 16 WF 1/2 90°	16	5/8"	1/2"				0.163
012092	S R 16 WF 5/8 90°	16	5/8"	5/8"				0.172
012089	S R 16 WF 3/4 90°	16	5/8"	3/4"				0.192
137047	S R 19 WF 1/2 90°	19	3/4"	1/2"				0.16
137048	S R 19 WF 5/8 90°	19	3/4"	5/8"				0.18
012227	S R 19 WF 3/4 90°	19	3/4"	3/4"				0.213
012224	S R 19 WF 1" 90°	19	3/4"	1"				0.295
034304	S R 25 WF 3/4 90°	25	1"	3/4"				0.36
012346	S R 25 WF 1" 90°	25	1"	1"				0.439
062777	S R 25 WFR 1"1/4 90°	25	1"	1"1/4				0.623
129771	S R 32 WFR 1"1/4 90°	32	1"1/4	1"1/4				0.38
062779	S R 32 WFR 1"1/2 90°	32	1"1/4	1"1/2				0.82
129785	S R 38 WFR 1"1/2 90°	38	1"1/2	1"1/2				0.38
062781	S R 38 WF 2" 90°	VOIR SERIE	WFRJ ou WFRV					0

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
129786	S R 50 WFR 2" 90°	50	2"	2"				0.38
054088	S R 50 WF 1"1/2 90°	50	2"	1"1/2				1.6
040325	S R 50 WF 2"1/2 90°	50	2"	2"1/2				1.548
040326	S R 63 WF 2"1/2 90°	63	2"1/2	2"1/2				2.633
040327	S R 76 WF 3" 90°	76	3"	3"				2.1