


Embout à sertir 90° femelle BSP - écrou à voile



DKOR 90° - CONE 60° - AVEC ECROU A VOILE ET JOINT

Matière: Acier

Montage: Avec ou sans dénudage

Norme: ISO 8434-6 (BS 5200).

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
061738	S R 5 WFRV 1/4 90°	5	3/16"	1/4"				0.04
029574	S R 6 WFRV 1/4 90°	6	1/4"	1/4"				0.046
029577	S R 6 WFRV 3/8 90°	6	1/4"	3/8"				0.059
061739	S R 6 WFRV 1/2 90°	6	1/4"	1/2"				0.07
029581	S R 8 WFRV 3/8 90°	8	5/16"	3/8"				0.07
061743	S R 8 WFRV 1/2 90°	8	5/16"	1/2"				0.079
029585	S R 10 WFRV 3/8 90°	10	3/8"	3/8"				0.072
060052	S R 10 WFRV 1/2 90°	10	3/8"	1/2"				0.095
061745	S R 13 WFRV 1/2 90°	13	1/2"	1/2"				0.128
061746	S R 13 WFRV 5/8 90°	13	1/2"	5/8"				0.13
061747	S R 13 WFRV 3/4 90°	13	1/2"	3/4"				0.1
061748	S R 16 WFRV 3/4 90°	16	5/8"	3/4"				0.2
029609	S R 19 WFRV 1" 90°	19	3/4"	1"				0.308
061750	S R 25 WFRV 1"1/4 90°	25	1"	1"1/4				0.582
061751	S R 32 WFRV 1"1/4 90°	32	1"1/4	1"1/4				0.715
061752	S R 32 WFRV 1"1/2 90°	32	1"1/4	1"1/2				0.851
061753	S R 38 WFRV 1"1/2 90°	38	1"1/2	1"1/2				1.02
061754	S R 38 WFRV 2" 90°	38	1"1/2	2"				1.39