

Embout à sertir femelle MÉTRIQUE cone 60°



DKM - DIN CONE 60°

Matière: Acier

Montage: Avec ou sans dénudage

Norme: ISO 8434-6 - DIN 3863

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
038108	S R 5 DF 12	5	3/16"	M12X150				0.023
038109	S R 6 DF 12	6	1/4"	M12X150				0.026
038107	S R 6 DF 14	6	1/4"	M14X150				0.03
029652	S R 6 DF 16	6	1/4"	M16X150				0.045
038110	S R 6 DF 18	6	1/4"	M18X150				0.04
038111	S R 8 DF 14	8	5/16"	M14X150				0.034
029650	S R 8 DF 16	8	5/16"	M16X150				0.047
029653	S R 8 DF 18	8	5/16"	M18X150				0.042
029655	S R 10 DF 14	10	3/8"	M14X150				0.037
038112	S R 10 DF 16	10	3/8"	M16X150				0.048
038113	S R 10 DF 18	10	3/8"	M18X150				0.044
038114	S R 10 DF 20	10	3/8"	M20X150				0.072
038115	S R 10 DF 22	10	3/8"	M22X150				0.067
038116	S R 13 DF 18	13	1/2"	M18X150				0.061
038117	S R 13 DF 20	13	1/2"	M20X150				0.08
038118	S R 13 DF 22	13	1/2"	M22X150				0.074
038119	S R 13 DF 26	13	1/2"	M26X150				0.115
021315	S R 16 DF 26	16	5/8"	M26X150				0.127
012124	S R 19 DF 26	19	3/4"	M26X150				0.137
012127	S R 19 DF 30	19	3/4"	M30X150				0
038557	S R 25 DF 38	25	1"	M38X150				0.38
038558	S R 32 DF 45	32	1 1/4"	M45X150				0.56
012461	S R 38 DF 52	38	1 1/2"	M52X200				0
012524	S R 50 DF 65	50	2"	M65X200				1.06