


Embout à sertir compact 90° femelle JIC



DKJ-K 90° - CONE 74°

Matière: Acier

Montage: Avec ou sans dénudage

Norme: ISO 8434-2 (SAE J514).

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
038567	S R 5 JF 7/16 90° CC	5	3/16"	7/16 - 20				0.317
097228	S R 6 JF 7/16 90° CC	6	1/4"	7/16 - 20				0.06
038568	S R 6 JF 1/2 90° CC	6	1/4"	1/2 - 20				0.714
137566	S R 6 JF 9/16 90° CC	6	1/4"	1/2 - 20				0.041
011602	S R 8 JF 9/16 90° CC	8	5/16"	9/16 - 18				0.08
011738	S R 10 JF 9/16 90° CC	10	3/8"	9/16 - 18				0.093
038570	S R 10 JF 3/4 90° CC	10	3/8"	3/4 - 16				0.102
011897	S R 13 JF 3/4 90° CC	13	1/2"	3/4 - 16				0.141
011901	S R 13 JF 7/8 90° CC	13	1/2"	7/8 - 14				0.17
038571	S R 16 JF 1"1/16 90° CC	16	5/8"	1"1/16 - 12				0.256
137567	S R 19 JF 1"1/16 90° CC	19	3/4"	1"1/16 - 12				0.277
038572	S R 19 JF 1"3/16 90° CC	19	3/4"	1"3/16 - 12				0.404
038573	S R 25 JF 1"5/16 90° CC	25	1"	1"5/16 - 12				0.527