


Embout à sertir 90° femelle JIC long - écrou serti



DKJ 90° - CONE 74° - LONG AVEC ECROU SERTI

Matière: Acier

Montage: Avec ou sans dénudage

Norme: ISO 8434-2 (SAE J514).

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
066150	S R 6 JF 7/16 90° L46	6	1/4"	7/16 - 20	46mm			0.036
072067	S R 6 JF 1/2 90° L45	6	1/4"	1/2 - 20	45mm			0.046
072068	S R 6 JF 9/16 90° L54	6	1/4"	9/16 - 18	54mm			0.053
035111	S R 8 JF 9/16 90° L54	8	5/16"	9/16 - 18	54mm			0.063
072070	S R 10 JF 9/16 90° L54	10	3/8"	9/16 - 18	54mm			0.076
072071	S R 10 JF 3/4 90° L64	10	3/8"	3/4 - 16	64mm			0.105
072072	S R 13 JF 3/4 90° L64	13	1/2"	3/4 - 16	64mm			0.128
096851	S R 13 JF 7/8 90° L32	13	1/2"	7/8 - 14	32mm			0.158
072073	S R 13 JF 7/8 90° L65	13	1/2"	7/8 - 14	65mm			0.158
072074	S R 16 JF 7/8 90° L65	16	5/8"	7/8 - 14	65mm			0.195
072075	S R 16 JF 1"1/16 90° L96	16	5/8"	1"1/16 - 12	96mm			0.245
072076	S R 19 JF 1"1/16 90° L96	19	3/4"	1"1/16 - 12	96mm			0.271
072077	S R 25 JF 1"5/16 90° L114	25	1"	1"5/16 - 12	114mm			0.56