

Embout à sertir male JIC



AGJ - CONE 74°

Matière: Acier

Montage: Avec ou sans dénudage

Norme: ISO 8434-2 (SAE J514).

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
035495	S R 2 JM 3/8	2	1/12"	3/8 - 24				0.01
035494	S R 2 JM 7/16	2	1/12"	7/16 - 20				0.016
035496	S R 2 JM 1/2	2	1/12"	1/2 - 20				0.016
035498	S R 3 JM 3/8	3	1/8"	3/8 - 24				0.012
035497	S R 3 JM 7/16	3	1/8"	7/16 - 20				0.018
035499	S R 3 JM 1/2	3	1/8"	1/2 - 20				0.032
031129	S R 4 JM 3/8	4	5/32"	3/8 - 24				0.012
035500	S R 4 JM 7/16	4	5/32"	7/16 - 20				0.018
035501	S R 4 JM 1/2	4	5/32"	1/2 - 20				0.032
011376	S R 5 JM 7/16	5	3/16	7/16 - 20				0.017
011474	S R 6 JM 7/16	6	1/4"	7/16 - 20				0.02
011473	S R 6 JM 1/2	6	5/16"	1/2 - 20				0.024
011475	S R 6 JM 9/16	6	3/8"	9/16 - 18				0.031
011606	S R 8 JM 1/2	8	5/16"	1/2 - 20				0.025
011608	S R 8 JM 9/16	8	3/8"	9/16 - 18				0.034
026113	S R 8 JM 5/8	8	5/16"	5/8 - 18				0.035
011607	S R 8 JM 3/4	8	5/16"	3/4 - 16				0.045
078613	S R 10 JM 1/2	10	3/8"	1/2" - 20				0.036
011748	S R 10 JM 9/16	10	3/8"	9/16 - 18				0.036
011746	S R 10 JM 5/8	10	3/8"	5/8 - 18				0.036
011745	S R 10 JM 3/4	10	1/2"	3/4 - 16				0.054
011747	S R 10 JM 7/8	10	3/8"	7/8 - 14				0.073
011915	S R 13 JM 3/4	13	1/2"	3/4 - 16				0.063
011916	S R 13 JM 7/8	13	5/8"	7/8 - 14				0.08
011914	S R 13 JM 1"1/16	13	3/4"	1"1/16 - 12				0.122
012069	S R 16 JM 7/8	16	5/8"	7/8 - 14				0.092
012068	S R 16 JM 1"1/16	16	3/4"	1"1/16 - 12				0.137
128007	S R 19 JM 7/8	19	3/4"	7/8 - 14				0
012213	S R 19 JM 1"1/16	19	3/4"	1"1/16 - 27				0.148
012214	S R 19 JM 1"3/16	19	3/4"	13/16 - 12				0.165
012215	S R 19 JM 1"5/16	19	3/4"	15/16 - 12				0.19
024450	S R 25 JM 1"1/16	25	1"	1"1/16 - 12				0.2
012334	S R 25 JM 1"5/16	25	1"	15/16 - 12				0.249
012335	S R 25 JM 1"5/8	25	1"	1"5/8 - 12				0.352
012428	S R 32 JM 1"5/8	32	11/4"	15/8 - 12				0.4
012429	S R 32 JM 1"7/8	32	11/4"	17/8 - 12				0.492

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
012494	S R 38 JM 1"7/8	38	1 1/2"	17/8 - 12				0.544
012534	S R 50 JM 2"1/2	50	2"	2 1/2 - 12				1.014