


Embout à sertir compact 90° femelle BSP



DKR-K 90° - CONE 60° - AVEC ECROU SERTI

Matière: Acier

Montage: Avec ou sans dénudage

Norme: ISO 8434-6 (BS 5200).

Code	Référence	Diamètre tuyau (mm)	Diamètre tuyau (pouce)	F (Filetage)	H (mm)	S (mm)	E (mm)	Poids
A JONC								
040807	S R 6 WFRJ 1/4 90° CC	6	1/4"	1/4"				0.07
075617	S R 10 WFJ 3/8 90° CC	10	3/8"	3/8"				0
093666	S R 19 WFJ 3/4 90° CC	19	3/4"	3/4"				0.231
SERTI								
011505	S R 6 WF 1/4 90° CC	6	1/4"	1/4"				0.056
011513	S R 6 WF 3/8 90° CC	6	1/4"	3/8"				0.1
011639	S R 8 WF 3/8 90° CC	8	5/16"	3/8"				0.12
011779	S R 10 WF 3/8 90° CC	10	3/8"	3/8"				0.089
011772	S R 10 WF 1/2 90° CC	10	3/8"	1/2"				0
011936	S R 13 WF 1/2 90° CC	13	1/2"	1/2"				0.147
012228	S R 19 WF 3/4 90° CC	19	3/4"	3/4"				0.249
021317	S R 25 WF 1" 90° CC	25	1"	1"				0