

Embout à souder série L et S



AVEC JOINT TORIQUE - RACCORD DIN CONE 24°

Matière: acier

Norme: ISO 8434-1 (DIN 2353)

Type: 1057

Raccord livré nu, sans bague et sans ecrou

Code	Référence	D1	D2	D3	Pression (Bar)	Poids
SERIE L						
031157	49DL15X2.5	15L - M22X150	2.5mm		315	0
031158	49DL18X2.5	18L - M26X150	2.5mm		315	0
030988	49DL22X2.5	22L - M30X200	2.5mm		160	0
030986	49DL28X2.5	28L - M36X200	2.5mm		160	0
031159	49DL35X3	35L - M45X200	3mm		160	0
031160	49DL42X3	42L - M52X200	3mm		160	0
SERIE S						
031155	49DS 6X2	6S - M14X150	2mm		630	0
031153	49DS 8X2	8S - M16X150	2mm		630	0
031152	49DS10X2	10S - M18X150	2mm		315	0
022291	49DS12X2.5	12S - M20X150	2.5mm		630	0
024453	49DS14X3	14S - M22X150	3mm		400	0
024177	49DS16X3	16S - M24X150	3mm		400	0
002227	49DS20X4	20S - M30X200	4mm		400	0
002228	49DS25X4	25S - M36X200	4mm		315	0
017891	49DS30X5	30S - M42X200	5mm		315	0
024454	49DS38X6	38S - M52X200	6mm		315	0