


Union male à souder série L et S



RACCORD DIN CONE 24°

Matière: acier

Norme: ISO 8434-1 (DIN 2353)

Type: 1055

Raccord livré nu, sans bague et sans ecrou

Code	Référence	D1	D2	D3	Pression (Bar)	Poids
SERIE L						
031668	4SDL 6/T10 NU	6L - M12X150	10mm		315	0
031670	4SDL 8/T12 NU	8L - M14X150	12mm		315	0
031671	4SDL10/T14 NU	10L - M16X150	14mm		315	0
031672	4SDL12/T16 NU	12L - M18X150	16mm		315	0
031673	4SDL15/T19 NU	15L - M22X150	19mm		315	0
031674	4SDL18/T22 NU	18L - M26X150	22mm		315	0
031675	4SDL22/T27 NU	22L - M30X200	27mm		160	0
031676	4SDL28/T32 NU	28L - M36X200	32mm		160	0
031677	4SDL35/T40 NU	35L - M45X200	40mm		160	0.235
031678	4SDL42/T46 NU	42L - M52X200	46mm		160	0
SERIE S						
031679	4SDS 6/T11 NU	6S - M14X150	11mm		630	0
031680	4SDS 8/T13 NU	8S - M16X150	13mm		630	0
031681	4SDS10/T15 NU	10S - M18X150	15mm		630	0
031682	4SDS12/T17 NU	12S - M20X150	17mm		630	0
031683	4SDS14/T19 NU	14S - M22X150	19mm		630	0
031684	4SDS16/T21 NU	16S - M24X150	21mm		400	0
031685	4SDS20/T26 NU	20S - M30X200	26mm		400	0
031686	4SDS25/T31 NU	25S - M36X200	31mm		400	0
031687	4SDS30/T36 NU	30S - M42X200	36mm		400	0
031688	4SDS38/T44 NU	38S - M52X200	44mm		315	0