

Mamelon male x male



Mamelon male x male

Utilisations : Fluides courants compatibles.

Matière : Fonte galvanisée

Limites de températures et PMS :

De -20°C à +120°C : PMS = 25 Bars

De +120°C à +300°C : PMS = 20 Bars

Code	Référence	D1	D2	Poids
EGAUX				
001390	280G 1/8	MALE 1/8	MALE 1/8	0
001389	280G 1/4	MALE 1/4	MALE 1/4	0.02
001394	280G 3/8	MALE 3/8	MALE 3/8	0.042
001388	280G 1/2	MALE 1/2	MALE 1/2	0.063
001393	280G 3/4	MALE 3/4	MALE 3/4	0.095
001385	280G 1"	MALE 1"	MALE 1"	0.154
001387	280G 1"1/4	MALE 1"1/4	MALE 1"1/4	0.208
001386	280G 1"1/2	MALE 1"1/2	MALE 1"1/2	0.235
001391	280G 2"	MALE 2"	MALE 2"	0.382
001392	280G 2"1/2	MALE 2"1/2	MALE 2"1/2	0.654
017999	280G 3"	MALE 3"	MALE 3"	0.765
018215	280L 3"	MALE 3"	MALE 3"	0.652
018000	280G 4"	MALE 4"	MALE 4"	1.29
INEGAUX				
001309	245G 1"X3/4	MALE 1"	MALE 3/4	0
077868	245G 3/8X1/4	MALE 3/8	MALE 1/4	0.025
018015	245G 1/2X1/4	MALE 1/2	MALE 1/4	0.04
018016	245G 1/2X3/8	MALE 1/2	MALE 3/8	0.065
052455	245G 3/4X3/8	MALE 3/4"	MALE 3/8"	0.087
001311	245G 3/4X1/2	MALE 3/4	MALE 1/2	0.09
001308	245G 1"X1/2	MALE 1"	MALE 1/2	0.129
018017	245G 1"1/4X1/2	MALE 1"1/4	MALE 1/2	0.232
018018	245G 1"1/4X3/4	MALE 1"1/4	MALE 3/4	0.165
018019	245G 1"1/4X1"	MALE 1"1/4	MALE 1"	0.17
018021	245G 1"1/2X3/4	MALE 1"1/2	MALE 3/4	0.24
018022	245G 1"1/2X1"	MALE 1"1/2	MALE 1"	0.23
018023	245G 1"1/2X1"1/4	MALE 1"1/2	MALE 1"1/4	0.273
018024	245G 2"X1"	MALE 2"	MALE 1"	0.476
018025	245G 2"X1"1/4	MALE 2"	MALE 1"1/4	0.446
018026	245G 2"X1"1/2	MALE 2"	MALE 1"1/2	0.38
049420	245G 2"1/2X1"1/2	MALE 2"1/2	MALE 1"1/2	0.66
001310	245G 2"1/2X2"	MALE 2"1/2	MALE 2"	0.665
057223	245G 3"X2"	MALE 3"	MALE 2"	0.99