

Manchon femelle x femelle



Manchon femelle x femelle

Utilisations : Fluides courants compatibles.

Matière : Fonte galvanisée

Limites de températures et PMS :

De -20°C à +120°C : PMS = 25 Bars

De +120°C à +300°C : PMS = 20 Bars

Code	Référence	D1	D2	Poids
EGAUX				
090106	240G 2"X1"1/2	FEM 2"	FEM 1"1/2	0.442
001341	270G 1/4	FEM 1/4	FEM 1/4	0.035
001344	270G 3/8	FEM 3/8	FEM 3/8	0.047
001340	270G 1/2	FEM 1/2	FEM 1/2	0.059
001343	270G 3/4	FEM 3/4	FEM 3/4	0.096
001337	270G 1"	FEM 1"	FEM 1"	0.14
001339	270G 1"1/4	FEM 1"1/4	FEM 1"1/4	0.202
001338	270G 1"1/2	FEM 1"1/2	FEM 1"1/2	0.329
001342	270G 2"	FEM 2"	FEM 2"	0.413
018001	270G 2"1/2	FEM 2"1/2	FEM 2"1/2	0.635
018002	270G 3"	FEM 3"	FEM 3"	0.921
001345	270G 4"	FEM 4"	FEM 4"	1.455
INEGAUX				
001271	240G 3/8X1/4	FEM 3/8	FEM 1/4	0.04
001264	240G 1/2X1/4	FEM 1/2	FEM 1/4	0.059
001265	240G 1/2X3/8	FEM 1/2	FEM 3/8	0.061
001270	240G 3/4X3/8	FEM 3/4	FEM 3/8	0.085
001269	240G 3/4X1/2	FEM 3/4	FEM 1/2	0.08
052453	240G 1"X3/8	FEM 1"	FEM 3/8"	0.14
001262	240G 1"X1/2	FEM 1"	FEM 1/2	0.145
001263	240G 1"X3/4	FEM 1"	FEM 3/4	0.149
084791	240G 1"1/4X3/8	FEM 1"1/4	FEM 3/8"	0.235
018027	240G 1"1/4X1/2	FEM 1"1/4	FEM 1/2	0.223
018028	240G 1"1/4X3/4	FEM 1"1/4	FEM 3/4	0.23
001266	240G 1"1/4X1"	FEM 1"1/4	FEM 1"	0.253
001260	240G 1"1/2X1/2	FEM 1"1/2	FEM 1/2	0.22
001261	240G 1"1/2X3/4	FEM 1"1/2	FEM 3/4	0.287
001258	240G 1"1/2X1"	FEM 1"1/2	FEM 1"	0.3
001259	240G 1"1/2X1"1/4	FEM 1"1/2	FEM 1"1/4	0.304
018029	240G 2"X1/2	FEM 2"	FEM 1/2	0.31
018030	240G 2"X3/4	FEM 2"	FEM 3/4	0.325
001268	240G 2"X1"	FEM 2"	FEM 1"	0.355
018031	240G 2"X1"1/4	FEM 2"	FEM 1"1/4	0.407
018032	240G 2"1/2X1"1/4	FEM 2"1/2	FEM 1"1/4	0.592

Code	Référence	D1	D2	Poids
018033	240G 2"1/2X1"1/2	FEM 2"1/2	FEM 1"1/2	0.605
018035	240G 2"1/2X2"	FEM 2"1/2	FEM 2"	0.63
018036	240G 3"X1"1/2	FEM 3"	FEM 1"1/2	0.73
018037	240G 3"X2"	FEM 3"	FEM 2"	0.73
018038	240G 3"X2"1/2	FEM 3"	FEM 2"1/2	0.8
018039	240G 4"X2"	FEM 4"	FEM 2"	1.2
018041	240G 4"X2"1/2	FEM 4"	FEM 2"1/2	1.2
001272	240G 4"X3"	FEM 4"	FEM 3"	1.2