

Manchon réduit femelle x male



Manchon réduit femelle x male

Utilisations : Fluides courants compatibles.

Matière : Fonte galvanisée

Limites de températures et PMS :

De -20°C à +120°C : PMS = 25 Bars

De +120°C à +300°C : PMS = 20 Bars

Code	Référence	D1	D2	Poids
MALEXFEM				
039902	246G 1/2X3/8	MALE 3/8"	FEM 1/2"	0.068
018044	246G 3/4X1/2	MALE 1/2"	FEM 3/4"	0.104
018046	246G 1"X1/2	MALE 1/2"	FEM 1"	0.144
024588	246G 1"1/4X1/2	MALE 1/2"	FEM 1"1/4"	0.205
018048	246G 1"X3/4	MALE 3/4"	FEM 1"	0.12
018050	246G 1"1/4X3/4	MALE 3/4"	FEM 1"1/4"	0.244
018051	246G 1"1/4X1"	MALE 1"	FEM 1"1/4"	0.245
018054	246G 1"1/2X1"	MALE 1"	FEM 1"1/2"	0.295
018055	246G 1"1/2X1"1/4	MALE 1"1/4"	FEM 1"1/2"	0.303
080907	246G 2"X1"1/4	MALE 1"1/4"	FEM 2"	0.303
039914	246G 2"X1"1/2	MALE 1"1/2"	FEM 2"	0.44