

## Coude 45° male x femelle



Coude 45° male x femelle

**Utilisations :** Fluides courants compatibles.

**Matière :** Fonte galvanisée

**Limites de températures et PMS :**

De -20°C à +120°C : PMS = 25 Bars

De +120°C à +300°C : PMS = 20 Bars

| Code   | Référence | D1         | D2        | Poids |
|--------|-----------|------------|-----------|-------|
|        |           | MALEXFEM   |           |       |
| 109816 | 40G 1/2   | MALE 1/2   | FEM 1/2   | 0.09  |
| 002043 | 40G 3/4   | MALE 3/4   | FEM 3/4   | 0.16  |
| 077871 | 40G 1"    | MALE 1"    | FEM 1"    | 0.23  |
| 037517 | 40G 1"1/4 | MALE 1"1/4 | FEM 1"1/4 | 0.385 |
| 022113 | 40G 1"1/2 | MALE 1"1/2 | FEM 1"1/2 | 0.485 |
| 002042 | 40G 2"    | MALE 2"    | FEM 2"    | 0.92  |
| 098458 | 40G 2"1/2 | MALE 2"1/2 | FEM 2"1/2 | 1.35  |
| 094105 | 40G 3"    | MALE 3"    | FEM 3"    | 2     |