

Raccord droit male conique



Raccord droit male conique

Matière : laiton nickelé
Utilisation : air comprimé
Pression max : 18 bars
Températures : -10°C à +70°C
 D1: diamètre tube rilsan associé

Code	Référence	D1	D2	Poids
130798	RPC UM02.7/4X1/8	2.7/4mm	1/8"	0.009
130803	RPC UM03/05X1/8	3/5mm	1/8"	0
129193	RPC UM04/06X1/8	4/6mm	1/8"	0.014
129194	RPC UM04/06X1/4	4/6mm	1/4"	0.02
129195	RPC UM04/06X3/8	4/6mm	3/8"	0.026
129197	RPC UM06/08X1/8	6/8mm	1/8"	0.02
129200	RPC UM06/08X1/4	6/8mm	1/4"	0.021
129202	RPC UM06/08X3/8	6/8mm	3/8"	0.028
129204	RPC UM06/08X1/2	6/8mm	1/2"	0.04
129205	RPC UM08/10X1/4	8/10mm	1/4"	0.02
129206	RPC UM08/10X3/8	8/10mm	3/8"	0.031
129207	RPC UM08/10X1/2	8/10mm	1/2"	0.043
129208	RPC UM10/12X3/8	10/12mm	3/8"	0.035
129209	RPC UM10/12X1/2	10/12mm	1/2"	0.045