

Raccord droit male cylindrique avec o'ring



Raccord droit male cylindrique avec o'ring

Matière : laiton nickelé
Utilisation : air comprimé
Pression max : 18 bars
Températures : -10°C à +70°C
 D1: diamètre tube rilsan associé

Code	Référence	D1	D2	Poids
130140	RPC UM02.7/04X1/8R	2.7/4mm	1/8"	0.009
129313	RPC UM04/06X1/8R	4/6mm	1/8"	0.015
129314	RPC UM04/06X1/4R	4/6mm	1/4"	0.022
129315	RPC UM04/06X3/8R	4/6mm	3/8"	0.027
129316	RPC UM04/06X1/2R	4/6mm	1/2"	0.043
129317	RPC UM06/08X1/8R	6/8mm	1/8"	0.18
129318	RPC UM06/08X1/4R	6/8mm	1/4"	0.023
129319	RPC UM06/08X3/8R	6/8mm	3/8"	0.029
129320	RPC UM08/10X1/4R	8/10mm	1/4"	0.027
129322	RPC UM08/10X3/8R	8/10mm	3/8"	0.032
129323	RPC UM08/10X1/2R	8/10mm	1/2"	0.048
129324	RPC UM10/12X3/8R	10/12mm	3/8"	0.027
129325	RPC UM10/12X1/2R	10/12mm	1/2"	0.051
129326	RPC UM04/06XM5R	4/6mm	M5	0.007
129327	RPC UM04/06XM6R	4/6mm	M6	0.07