

Raccord droit femelle



Raccord droit femelle

Matière : laiton nickelé
Utilisation : air comprimé
Pression max : 18 bars
Températures : -10°C à +70°C
D1: diamètre tube rilsan associé

Code	Référence	D1	D2	Poids
130947	RPC UF02.7/4X1/8	2.7/4mm	1/8"	0.012
130948	RPC UF03/05X1/8	3/5mm	1/8"	0.012
129328	RPC UF04/06X1/8	4/6mm	1/8"	0.017
129329	RPC UF04/06X1/4	4/6mm	1/4"	0.023
129330	RPC UF04/06X3/8	4/6mm	3/8"	0.037
129331	RPC UF06/08X1/8	6/8mm	1/8"	0.019
129332	RPC UF06/08X1/4	6/8mm	1/4"	0.026
129333	RPC UF06/08X3/8	6/8mm	3/8"	0.039
129334	RPC UF06/08X1/2	6/8mm	1/2"	0.042
129335	RPC UF08/10X1/4	8/10mm	1/4"	0.028
129336	RPC UF08/10X3/8	8/10mm	3/8"	0.042
129337	RPC UF08/10X1/2	8/10mm	1/2"	0.043
130951	RPC UF08/10X1/8	8/10mm	1/8"	0.025
129338	RPC UF10/12X3/8	10/12mm	3/8"	0.047