

Raccord droit male cylindrique



Raccord droit male cylindrique

Matière : laiton nickelé
Utilisation : air comprimé
Pression max : 18 bars
Températures : -10°C à +70°C
D1: diamètre tube rilsan associé

Code	Référence	D1	D2	Poids
129595	RPCL04/06 GM1/8R	4/6mm	1/8"	0.034
129597	RPCL04/06 GM1/4R	4/6mm	1/4"	0.032
129598	RPCL04/06 GM3/8R	4/6mm	3/8"	0.036
129600	RPCL04/06 GM1/2R	4/6mm	1/2"	0.03
129618	RPCL06/08 GM1/8R	6/8mm	1/8"	0.042
129619	RPCL06/08 GM1/4R	6/8mm	1/4"	0.04
129620	RPCL06/08 GM3/8R	6/8mm	3/8"	0.044
129621	RPCL06/08 GM1/2R	6/8mm	1/2"	0.038
129622	RPCL08/10 GM1/4R	8/10mm	1/4"	0.022
129623	RPCL08/10 GM3/8R	8/10mm	3/8"	0.024
129624	RPCL08/10 GM1/2R	8/10mm	1/2"	0.02
129625	RPCL10/12 GM3/8R	10/12mm	3/8"	0.028
129626	RPCL10/12 GM1/2R	10/12mm	1/2"	0.026